

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2001198462 A**(43) Date of publication of application: **24.07.01**


(51) Int. Cl. **B01J 23/58**
B01D 53/94
B01J 23/40
B01J 23/42
B01J 23/63
F01N 3/10

(21) Application number: **2000011597**(71) Applicant: **TOYOTA MOTOR CORP**(22) Date of filing: **20.01.00**(72) Inventor: **MINAMI MITSURU**(54) **CATALYST FOR EXHAUST-GAS PURIFICATION**

(57) Abstract:

PROBLEM TO BE SOLVED: To improve NOx-purification efficiency by increasing a carrying density of a precious metal around an NOx-occlusion substance.

SOLUTION: A porous oxide layer 11 is formed at least partly on NOx- occlusion substance particles 10, and a precious metal 12 is carried on the oxide layer 11. Since the particles 10 and the precious metal 12 are placed closely to each other, and also the density of the carried precious metal 12 near the NOx-occlusion substance particles 10 is made high, the NOx-occlusion reaction and the reduction reaction are accelerated.



COPYRIGHT: (C)2001,JPO